



York Manufacturing
SUSTAINABLE MATERIALS DATA SHEET
Page 1 of 2
Effective Date: 5-11-2020

SUSTAINABLE MATERIALS DATA SHEET (See SDS sheet for further information)

SECTION 1.	PRODUCT & COMPANY IDENTIFICATION
------------	----------------------------------

PRODUCT NAME: **York Flash-Vent Max**

PRODUCT USE: Flashing membrane with integral non-woven drainage material. It is used as through-wall flashing, and as a flashing & drainage plane material.

MANUFACTURED BY: York Manufacturing
43 Community Dr.
Sanford, ME 04073
800-551-2828 (Technical Information)

SECTION 2.	RECYCLED CONTENT (Percentages are by Weight and Vary by Location) (*LEED® Recycled Content Credit 4.1)
------------	---

Fabric:

Total recycled Content	93%
Post Industrial Recycled Content	93%
Post-Consumer Recycled Content	0%

SECTION 3.	LOCAL/REGIONAL MATERIALS (*LEED Local/Regional Materials Credits 5.1 & 5.2)
------------	---

Please determine the distance in statute miles to your project site from our plant location in Sanford, Maine, 04073

SECTION 4.	PRODUCT RESISTS THE DEVELOPMENT & SPREAD OF INDOOR CONTAMINANTS (*LEED Innovation in Design Process Credit)
------------	--

When tested as manufactured, the product resists the growth of mold according to the test method ASTM D 3273-94. It may qualify for a LEED Innovation Credit based upon the environmental mitigation of mold and mildew hazards related to Indoor Air Quality (IAQ).

The “Construction IAQ Management Plan” (Credit 3) uses the “EPA Protocol for Environmental Requirements, Baseline IAQ and Materials for Research Triangle Park Campus, Section 01445” (www.epa.gov/rtp/new-bldg/environmental/s_01445.htm) as one of its reference standards. It incorporates a measurement for airborne Mold & Mildew, which includes:

1. “Compliance Indoor air quality shall conform to the following standards and limits.”
2. “Airborne Mold and Mildew: Simultaneous indoor and outdoor readings.”

This Specification section was a part of the construction documents for the EPA’s Research & Administration Facility at Research Triangle Park. The section addresses baseline indoor air quality testing and materials testing.”

Note: one of the five areas covered to protect against IAQ problems is through “Source Control” of materials. That could be a potential hindrance to passing the testing phase of the IAQ mentioned above LEED Reference Standard. Specifying products that score well on the ASTM D 3273-94 Mold Test may provide an effective method for protecting IAQ.

***All LEED® rating point references are suggested applications of York’s copper flashing systems to the LEED rating system. LEED applicants should use their objective determinations of product attributes for LEED certification purposes.**

For more information call Technical Services 1-800-551-2828 between 8:00 AM – 5:00 PM Mon – Fri Eastern Time

LEED is a registered trademark of the U.S. Green Building Council.