# Wasco-Seal® Plus

## Flexible Membrane

## Key Properties

- ARC coating surface for better adhesion to sealants and adhesives
- Better than Wasco-Seal
  - 5 times the breaking strength
  - 7 times the burst strength
  - 14 times the tear strength
  - 3.6 times the puncture resistance
- No plasticizers
  - Does not become brittle or crack
- Flexible, easy to cut and form by hand
- 3-year UV exposure: to prevent damage, the product must be concealed within 180 days

**Available in:**
12", 16", 18", 24", 36" x 150'
**Custom sizes upon request.**

NSF

Certified to NSF/ANSI/CAN 61

## Description

**Wasco-Seal® Plus** has been designed with a flexible sheet of waterproof, cross woven polyethylene with an ARC coating. The ARC provides UV resistance, and a great surface for sealants and adhesives to adhere to.

## Compatible With

- Air barriers
- Below grade waterproofing
- Roofing membranes
- Construction sealants and adhesives

## Joining of Material

Joint shall be made by lapping a minimum of 6" and coating the contacting surfaces with a construction adhesive or sealant, like York's UniverSeal US-100.

| | Wasco-Seal® Plus | Wasco Seal® (Original) |
|---|---|---|
| Abrasion, Tear and Puncture Resistant | ★★★★★ | ★ |
| Sealant and Adhesive Compatibility | ★★★★★ | ⊘ |
| Long-Term Flexibility | ★★★★★ | ★ |
| UV Exposure | ★★★★★ | ★ |
| Ease of Installation | ★★★★★ | ★★★ |
| Longevity | ★★★ | ★ |
| Price | $ | $ |

BEST VALUE