



Product Substitution Request

Submitted To: _____

Project: _____

Specified Item: _____

Specification Section: **Masonry Flashing/Accessories**

Proposed Substitution: **Wicked Good Flashing and Transition Membrane**

Performance Characteristics		
	Rubberized Asphalt	Wicked Good Flashing and Transition Membrane
Base Material	Asphalt	Butyl
Puncture (ASTM E154)	80 psi	400 psi
Tensile Strength (ASTM D412)	1,200 psi	4,000 psi min.
UV Exposure	30 days	6 months
Primer Required	Yes	No
Application Temperature	40°F to 120°F	20° F to 170° F

Technical data sheet includes product description, specifications, performance and test data adequate for evaluation of the request. If not present, is available at www.yorkflashings.com or 1-800-551-2828

The undersigned certifies that the following paragraphs, unless modified by attachments, are correct:

1. The proposed substitution does not affect dimensions shown on drawings.
2. The proposed substitution will have no adverse effect on the other trades, the construction schedule, or specified warranty requirements.
3. Local support and availability will be available for proposed substitution.
4. Mock-up wall materials available upon request.

The undersigned further states that the function and quality of the proposed product substitution is equivalent or superior to the specified item.

SUBMITTED BY

Name: _____ Title: _____

Firm: _____ Address: _____

Phone: _____ E-mail: _____

Signature: _____ Date: _____

Remarks: _____

A&E REVIEW

- Accepted
- Not Accepted
- Accepted as noted

Remarks: _____

Reviewed by: _____ Date: _____