

Wasco Seal®

Elastomeric Sheeting

Key Properties

- Intended for use as a concealed waterproofing membrane on foundation walls and under concrete slabs
- Wasco Seal should not be permanently exposed to sunlight, weather or traffic. Maximum exposure time is 30 days
- Recommended for concealed applications only
- Ideal for air and dust barriers, basement walls, and basement floors
- Color: Black

Description

Wasco Seal® has a non-reinforced polymeric, waterproofed, impermeable sheet, composed of elastomeric substances which have been reduced to a thermoplastic state and formed into a continuous sheet available in the following thicknesses:

Type 20(.020") weighing approx. 22 ounces per sq. yd.

Type 30(.030") weighing approx. 33 ounces per sq. yd.

Joining of Material

Joint shall be made by lapping a minimum of 6" and coating the contacting surfaces with a rubber cement.

Available in:

12", 16", 18", 24", 36" widths

Type 20 rolls are 150' long

Type 30 rolls are 100' long

Custom sizes upon request.

Wasco Seal Plus®

Flexible Membrane

Key Properties

- ARC coating surface for better adhesion to sealants and adhesives
- Better than Wasco Seal
 - 5 times the breaking strength
 - 7 times the burst strength
 - 14 times the tear strength
 - 3.6 times the puncture resistance
- No plasticizers
 - Does not become brittle or crack
- Flexible, easy to cut and form by hand
- 3-year UV exposure: to prevent damage, product must be concealed within 180 days

Description

Wasco Seal Plus® has been designed with a flexible sheet of cross woven polyethylene with an ARC coating. The ARC provides UV resistance, and a great surface for sealants and adhesives to adhere to.

Compatible With

- Air barriers
- Below grade waterproofing
- Roofing membranes
- Construction sealants and adhesives

Joining of Material

Joint shall be made by lapping a minimum of 6" and coating the contacting surfaces with a construction adhesive or sealant, like York's UniverSeal US-100.

Available in:

12", 16", 18", 24", 36" x 150'

Custom sizes upon request.